

**GAS SENSORS FOR RFG 651/2/3 AND RFG 361**

**SRD ... - SRS ...**



**APPLICATION**

Monitor the concentration of combustible gas or carbon monoxide in the air and activate a voltage output to the electronic detector. Housing in plastic material. Wall mounting.

Complies with CEI EN 50194 and CEI EN 50244 regulations.

**Features**

- Power supply: 12 V- (from the detector); Consumption: 150 mA; Output signal: 0 ... 5 V-.

Code	Case	Protect.	Connection length		Data sheet
			3 x 1 mm <sup>2</sup>	3 x 1,5 mm <sup>2</sup>	
<b>SRD 150</b>	Domestic (80 x 80 x 35 mm)	IP 20	50 mt.	75 mt.	-
<b>SRD 250</b>	Domestic (80 x 80 x 35 mm)	IP 20	50 mt.	75 mt.	-
<b>SRD 350</b>	Domestic (80 x 80 x 35 mm)	IP 20	50 mt.	75 mt.	-
<b>SRS 150</b>	Commercial (80 x 80 x 42)	IP 44	50 mt.	75 mt.	-
<b>SRS 250</b>	Commercial (80 x 80 x 42 mm)	IP 44	50 mt.	75 mt.	-
<b>SRS 350</b>	Commercial (80 x 80 x 42 mm)	IP 44	50 mt.	75 mt.	-